

Technical Data Sheet



Product Name:

Primer Adhesive for Attrition Coatings

Product Number:

NML52

Product Description:

NML 52 Grey is a single packaging adhesive primer for use with attrition coatings.

Approvals/Specifications:

- MSRR 9072
 - Rolls Royce Code: 139116
 - OMA 7 / 82
 - MTU: MTS 1026A
 - NSN: 8010-99-799-9449
 - RPS 340 / 4
 - Turbomecca to LB 538
-

Performance:

Double lap shear strength at 180°C (355°F) will be not less than 5086 MPa.

Components:

Single Pack Product.

Application:**Surface Preparation:**

All surfaces should be thoroughly clean, oil and grease should be removed using an approved solvent cleaner.

The importance of Cleanliness cannot be over emphasised for bonded surfaces. Any dirt, grease or other contaminants on the bonded surfaces will result in unsatisfactory bonding

Paint Preparation:

Supplied Ready for use – mix thoroughly before application

Application Method:

Apply to RPS 340 / 4

May be spread by non-metallic spatula, brush or applied via a glue gun method.

Technical Data Sheet



Drying Curing:

Apply a thin coat and stove at 125°C (255°F) ± 5°C (40°F) for 20 minutes.

Technical Properties:

Supply Viscosity:	Ready for use
Flash Point:	4°C
VOC Content:	N/A
Colour:	As Supplied
Pack Size:	250ml
Density:	1.11 g/ml
Gloss:	N / A
Thinner:	Methyl Ethyl Ketone (MEK)
Solvent/Clean Up:	MEK
Catalyst:	N / A
Theoretical Coverage:	7 sq m/kg @ 80 micron

Storage:

Store refrigerated, preferably frozen for maximum shelf life
At 20°C – 12 weeks
Minus 15°C – 12 months

Before use, refer to Product Safety Data Sheet

Disclaimer:

The information printed in this publication is based upon the research and experience of Indestructible Paint Ltd. No representation of warranty is made, however, concerning the accuracy or completeness of the information presented in this publication. Indestructible Paint Ltd make no warranty or representation of any kind, express or implied. Including without information limitation any warranty or merchantability or fitness for any particular purpose, and no warranty or representation shall be implied by law or otherwise. Any products sold by Indestructible Paint Ltd are not warranted as suitable for any particular purpose to the buyer. The suitability of any products for any purpose in particular to the buyer is for the buyer to determine. Indestructible Paint Ltd assumes no responsibility for the selection of products suitable to the particular purpose of any particular buyer. Indestructible Paint Ltd shall in no event be liable for any special, incidental or consequential damages.

Safety Data Sheets:

For Safety Data Sheets please contact our Sales Department:

Tel: +44(0)121 702 2485

Email: sales@indestructible.co.uk
