

# Technical Data Sheet



---

<b>Product Name:</b>	Anti Spatter Lacquer for use with Electron Beam Welding
----------------------	---

---

<b>Product Number:</b>	PL200
------------------------	-------

---

<b>Product Description:</b>	Green tinted lacquer for use to aid the removal of weld spatters when used with electron beam welders.
-----------------------------	--

---

<b>Approvals/Specifications:</b>	<ul style="list-style-type: none"><li>- CSS 196</li><li>- PMC 2056-1</li><li>- Rolls Royce Code: 148241</li><li>- OMat 3/171</li><li>- OMat 3/37C</li></ul>
----------------------------------	---

---

<b>Performance:</b>	<ul style="list-style-type: none"><li>- Green tinted lacquer for use to aid the removal of weld spatters when used with electron beam welders</li><li>- Designed to ensure that after application, the affected surface shall be free of masking paint and no evidence of vaporised metal or weld spatter after welding in accordance with RPS 388 electron beam welding or alternative and removal of lacquer and spatter in accordance with RPS 461.</li><li>- As a protection against adherent weld spatter this material has been tested to ensure that no deleterious effects on these materials occur.</li><li>- Removable with vapour degreasing or strong solvents</li><li>- Tested to ensure no damage to underlying metal.</li></ul>
---------------------	--

---

<b>Components:</b>	Single Pack Product.
--------------------	----------------------

---

# Technical Data Sheet



---

## Application:

Surface Preparation:	Clean and degrease in accordance with RPS 461 or suitable alternative
Paint Preparation:	Ensure lacquer is well shaken/ stirred before use
Application Method:	Spray, dip or brush applied and dries within minutes. Do not apply at temperatures below 5°C (40°F) and relative humidities above 75%.  Preferred range 15-30°C (60-85°F) and 35-75% RH.
Drying Curing:	Air dry one pack material.

---

## Technical Properties:

Supply Viscosity:	18 ± 2 / ISO Cup 5 Cup
Flash Point:	24°C
VOC Content:	N/A
Colour:	Green
Pack Size:	5 Litres
Density:	0.900kg/l
Gloss:	N/A
Thinner:	N/A
Solvent/Clean Up:	42000
Catalyst:	N/A.
Theoretical Coverage:	-

---

## Storage:

Highly flammable liquid: store and use in accordance with the flammable liquid regulations

**Shelf Life:** 12 months temperate; 6 months tropical

**Before use, refer to Product Safety Data Sheet**

---

## Disclaimer:

The information printed in this publication is based upon the research and experience of Indestructible Paint Ltd. No representation of warranty is made, however, concerning the accuracy or completeness of the information presented in this publication. Indestructible Paint Ltd make no warranty or representation of any kind, express or implied. Including without information limitation any warranty or merchantability or fitness for any particular purpose, and no warranty or representation shall be implied by law or otherwise. Any products sold by Indestructible Paint Ltd are not warranted as suitable for any particular purpose to the buyer. The suitability of any products for any purpose in particular to the buyer is for the buyer to determine. Indestructible Paint Ltd assumes no responsibility for the selection of products suitable to the particular purpose of any particular buyer. Indestructible Paint Ltd shall in no event be liable for any special, incidental or consequential damages.

---

## Safety Data Sheets:

For Safety Data Sheets please contact our Sales Department:

Tel: +44(0)121 702 2485

Email: [sales@indestructible.co.uk](mailto:sales@indestructible.co.uk)