Technical Data Sheet



| Product Name: | Aerosol Packed Binder for Powdered Brazing Alloys |
|---------------------------|--|
| Product Number: | PL248 |
| Product Description: | Aerosol packed acrylic lacquer for brazing operations and as a general protective coating for use in furnace brazing operations to RPS 194. The binders have been used extensively with various braze powders for many years. As well as binding the powder they must have virtually zero residue and burn off cleanly during the braze cycle. The PL binders PL248 and PL246 satisfy these requirements hence their approval and use by RR |
| Approvals/Specifications: | Rolls Royce Spec CSS 189 RR Code 139094 OMat 3/38F |
| Performance: | For use as a binder when compounded with powder brazing alloys |
| | Used for holding powder in place on Honeycomb aeroengine parts |
| | - Seals metal, wood, plastic and paper surfaces with a flexible film |
| | - It seals against fresh and salt water air and chemicals. |
| | - It helps prevent tarnishing of copper, brass and ferrous metals |
| | - It is non-yellowing material |
| Components: | Single Pack Product |
| Application: | |
| Surface Preparation: | Ensure that all surfaces to be applied to are dirt, oil and grease |

Technical Data Sheet



free.

Paint Preparation: Shake aerosol well before use.

Application Method: Apply to RPS 194

Drying Curing: Air drying lacquer

Technical Properties: Supply Viscosity: Ready for Use

Flash Point:

VOC Content: -

Colour: Clear

Pack Size: 400ml aerosols

Density: 0.900 +/- 0.015kg/l

Gloss: Gloss

Thinner: Supplied R.F.U. in aerosol

Solvent/Clean Up: 40020

Catalyst: N/A

Theoretical Coverage: -

Storage: Highly flammable liquid: store and use in accordance with the

flammable liquid regulations

Shelf Life: 12 months temperate; 6 months tropical

Before use, refer to Product Safety Data Sheet

Disclaimer:

The information printed in this publication is based upon the research and experience of Indestructible Paint Ltd. No representation of warranty is made, however, concerning the accuracy or completeness of the information presented in this publication. Indestructible Paint Ltd make no warranty or representation of any kind, express or implied. Including without information limitation any warranty or merchantability or fitness for any particular purpose, and no warranty or representation shall be implied by law or otherwise. Any products sold by Indestructible Paint Ltd are not warranted as suitable for any particular purpose to the buyer. The suitability of any products for any purpose in particular to the buyer is for the buyer to determine. Indestructible Paint Ltd assumes no responsibility for the selection of products suitable to the particular purpose of any particular buyer. Indestructible Paint Ltd shall in no event be liable for any special, incidental or consequential damages.

Technical Data Sheet



Safety Data Sheets:

For Safety Data Sheets please contact our Sales Department:

Tel: +44(0)121 702 2485

Email: sales@indestructible.co.uk