## **Technical Data Sheet**



Product Name:	Green Tinted Stop Off Lacquer	
Product Number:	PL81-2438-099	
Product Description:	Temporary protective stop-off laquer and insulating varnish	
Approvals/Specifications:	See PL106 + PL81-R3	
Performance:	- A very fast-drying coating.	
	- Used for plating insulation, as a temporary protective stop off lacquer and as an insulating varnish.	
	- This product has a good protection against hydrofluoric and nitric acid and also hot plating solutions.	
	<ul> <li>It has been used as a maskant for protection against electroless nickel plating. It withstands 4 hours at 95°C.</li> </ul>	
	<ul> <li>PL81-2438-099 is removable by immersion in strong solvent.</li> <li>IP9286-THIN has been used successfully.</li> </ul>	
Components:	1 or 5 litre cans	
Application:		
Surface Preparation:	See below.	
Paint Preparation:	Shake/ stir well before use	
Application Method:	Can be sprayed, brushed or dipped on to a clean, grease and oil free surface.	
	Removal IP9286-THIN. Straight Ketones, e.g. MEK will remove or Trike bath.	
Drying Curing:	<b>Air dry:</b> - Touch dry in approx. 10 -15 minutes	

Indestructible Paint Ltd, 16-25 Pentos Drive, Sparkhill, Birmingham B11 3TA Tel: +44(0)121 702 2485, Fax: +44 (0)121 778 4338, E-Mail: <u>sales@indestructible.co.uk</u>, Web: <u>www.indestructible.co.uk</u> Registered in England: 1376995

## **Technical Data Sheet**



<b>Technical Properties:</b>	Supply Viscosity:	B3 @ 20°C 20-30 seconds		
	Flash Point:	4°C/3/Paint UN 1263/PKG		
	VOC Content:	Group 11 -		
	Colour:	Green Tint		
	Pack Size:	1 and 5 Litre containers		
	Density:	0.840 +/- 0.015kg/l		
	Gloss:	N/A		
	Thinner:	Supplied Ready for Use		
	Solvent/Clean Up:	IP9286-THIN		
	Catalyst:	N/A		
	Theoretical Coverage:			
Storage:	Highly flammable liquid: store	Highly flammable liquid: store and use in accordance with the		
	flammable liquid regulations			
	Shelf Life: 12 months tempera	ate; 6 months tropical		
	Before use, refer to Product	Safety Data Sheet		
Disclaimer:	Indestructible Paint Ltd. No represent accuracy or completeness of the infor Paint Ltd make no warranty or represe without information limitation any warr purpose, and no warranty or represen products sold by Indestructible Paint L purpose to the buyer. The suitability of buyer is for the buyer to determine. In the selection of products suitable to the	The information printed in this publication is based upon the research and experience of Indestructible Paint Ltd. No representation of warranty is made, however, concerning the accuracy or completeness of the information presented in this publication. Indestructible Paint Ltd make no warranty or representation of any kind, express or implied. Including without information limitation any warranty or merchantability or fitness for any particular purpose, and no warranty or representation shall be implied by law or otherwise. Any products sold by Indestructible Paint Ltd are not warranted as suitable for any particular purpose to the buyer. The suitability of any products for any purpose in particular to the buyer is for the buyer to determine. Indestructible Paint Ltd assumes no responsibility for the selection of products suitable to the particular purpose of any particular buyer. Indestructible Paint Ltd shall in no event be liable for any special, incidental or consequential damages.		
Safety Data Sheets:	ty Data Sheets: For Safety Data Sheets please contact our Sales Departmen Tel: +44(0)121 702 2485			
	Email: sales@indestructible.c			

Indestructible Paint Ltd, 16-25 Pentos Drive, Sparkhill, Birmingham B11 3TA Tel: +44(0)121 702 2485, Fax: +44 (0)121 778 4338, E-Mail: <u>sales@indestructible.co.uk</u>, Web: <u>www.indestructible.co.uk</u> Registered in England: 1376995