# **Technical Data Sheet**



Product Name:	32000 Series		
Product Number:	32xxx – Primer,	32xxx – Primer, Undercoat and Topcoat variants	
	Primers:	Zinc Phosphate for metal	
	orc.	Wood Primer White	
	Undercoats:	White; Cream; Red; Blue; Light Grey; Dark Grey	
	Gloss Finishes:	White; Black and a full range of colours to include Creams; yellows; blues; reds; greys; greens; browns	
		All colours formulated where possible on lead free pigments	
	For full colour availability and pack sizes please consult your sales contact		
Product Description:	High Performance Air Drying Alkyd Systems. Resistant to Oils and Lubricants. Excellent Exterior Durability. Suitable for Brush or Spray Application. Ideal for Agricultural Equipment; Machinery; Racking Systems; Skips; General Metal Finishing; Marine and Exterior and Interior Wood Finishing		
Approvals/Specifications:	N/A		
Performance:	Reisists: - Engine Oil - Diesel Fuel - Petrol - Anti-Freeze		
Components:	Single component coating designed for Brush application. Supplied ready for use may be thinned with White Spirit if required.		

## **Technical Data Sheet**



### **Application:**

Surface Preparation: Surfaces must be clean and grease free. When over painting

existing paint a light abrasion with wet & dry paper will greatly

enhance adhesion.

Paint Preparation: Stir well before use.

Application Method: Intended for brush application. Supplied ready for use.

Drying Curing: Air drying

Touch Dry: 3-4 hours
Handleable: 6-8 hours
Hard Dry for Packing: Overnight

**Technical Properties:** Supply Viscosity: 120 – 180 s, ISO5, @ 23°C

Flash Point: ≥32°C

VOC Content: circa 550 g/lt

Colour: Variant specific

Pack Size: 2.5 and 5 litre

**Density:** 0.95 – 1.03kg/l colour specific

Gloss: Variant specific

Thinner: White Spirit

Solvent/Clean Up: 40006

Catalyst: N/A

Theoretical Coverage: 11-12 sq/m litre

Storage: Highly flammable liquid: store and use in accordance with the

flammable liquid regulations

Shelf Life: 12 months temperate; 6 months tropical

Before use, refer to Product Safety Data Sheet

### **Technical Data Sheet**



#### **Disclaimer:**

The information printed in this publication is based upon the research and experience of Indestructible Paint Ltd. No representation of warranty is made, however, concerning the accuracy or completeness of the information presented in this publication. Indestructible Paint Ltd make no warranty or representation of any kind, express or implied. Including without information limitation any warranty or merchantability or fitness for any particular purpose, and no warranty or representation shall be implied by law or otherwise. Any products sold by Indestructible Paint Ltd are not warranted as suitable for any particular purpose to the buyer. The suitability of any products for any purpose in particular to the buyer is for the buyer to determine. Indestructible Paint Ltd assumes no responsibility for the selection of products suitable to the particular purpose of any particular buyer. Indestructible Paint Ltd shall in no event be liable for any special, incidental or consequential damages.

**Safety Data Sheets:** 

For Safety Data Sheets please contact our Sales Department:

Tel: +44(0)121 702 2485

Email: sales@indestructible.co.uk