
Product Name:	Waterbased 2 Pack Polyurethane Lacquer
Product Number:	47200
Product Description:	A 2 pack component waterbased lacquer based entirely on a polyurethane dispersion. This product has very good chemical and abrasion resistance.

Technical Information:

Gloss:	30%
Colour:	Clear
Flash Point:	Non-Flammable
Storage Life:	12 months from date of manufacture. Protect from frost
Viscosity:	30 seconds B4 @ 20°C
Weight Solids:	30%
VOC Content:	42gms/ltr (inc water)
Mixing Ratio:	10:1 by volume with 47202
Thinners:	Up to 2% clean water if required
Application:	Two or three coats by spray, brush or squeegee. Must be sanded between coats with 180 or 220 grit paper.
Substrate:	Internal hardwood or softwood floors
Substrate Preparation:	The substrate must be clean, dry and free from contamination. Pre-sand with 120 or 150 grit paper
Drying Times:	Touch-dry 60 minutes. Allow 3 hours prior to sanding and recoating, under normal conditions (20°C/60% rh). Allow 24 hours before being subjected to traffic
Curing Times:	N/A
Pot Life:	N/A
Wet Film Thickness:	90 microns
Dry Film Thickness: (Approx per coat)	25 microns
Theoretical Coverage:	10-12m ² /l
Typical Performance:	The product is designed for application to internal hardwood or softwood floors which require high performance requirements
Application Advice:	Cleaning procedure for the dried film as follows. Mop with dilute detergent solution (not bleach or peroxide). Mop down the surface with clean water then dry.