Technical Data Sheet



Product Name:	Erosion Resistant Coating	
Product Number:	Adiprene-LW-520 / Ethacure 100	
Product Description:	Poly-ether based liquid coating prepared with an aliphatic diisocyanate that yields a tough flexible coating	
Approvals/Specifications:	MSRR 9212 / MSRR 1040	
Performance:	Clear Erosion Resistant coating for use as an abrasion and erosion resitant coating. Typically used as protestive coating where composite components require protection from rain and sand erosion.	
Components:	Two component product. Mixing Ratio: 10 parts Adiprene-LW-520 to 1 part Ethacure 100 parts by volume (100 : 9.7 parts by weight). Note pot life is temperature dependent; at elevated temperatures the pot life can be reduced to a few minutes	
Application:		
Surface Preparation:	Ensure surfaces to be coated are clean and free from dust, dirt etc. Typically applied over MSRR 9064 epoxy primer and colour coats.	
Paint Preparation:	Adiprene-LW-520 is supplied as a high viscous material at room temperature. Pre-heat in a water batch to reduce viscosity for mixing and application	
Application Method:	Apply by spray; can be sprayed at elevated temperature or thinned as required with thinner 665-550-025 or MEK	
Drying Curing:	Flash off: 10 minutes Full cure achieved after 16-24 hours	

Indestructible Paint Ltd, 16-25 Pentos Drive, Sparkhill, Birmingham B11 3TA Tel: +44(0)121 702 2485, Fax: +44 (0)121 778 4338, E-Mail: <u>sales@indestructible.co.uk</u>, Web: <u>www.indestructible.co.uk</u> Registered in England: 1376995

Technical Data Sheet



Technical Properties:	Supply Viscosity:	10,000-16,000 cps @ 50°C
		900-1,000 cps @ 100°C
	Flash Point:	N/A
	VOC Content:	0 g/litre
	Colour:	Clear
	Pack Size:	Adiprene 1 kg, Ethacure 500g
	Density:	Adiprene 1.03 kg/litre Ethacure 1.02 kg/litre
	Gloss:	Glossy
	Thinner:	665-550-025 or MEK
	Solvent/Clean Up:	40006 Gun Cleaner
	Catalyst:	Use as Kit
	Theoretical Coverage:	10 sq m/litre @ 1000 microns
Storage:	Highly flammable liquid: store and use in accordance with the flammable liquid regulations	
	Shelf Life: 12 months tempera Before use, refer to Product	
Disclaimer:	The information printed in this publication is based upon the research and experience of Indestructible Paint Ltd. No representation of warranty is made, however, concerning the accuracy or completeness of the information presented in this publication. Indestructible Paint Ltd make no warranty or representation of any kind, express or implied. Including without information limitation any warranty or merchantability or fitness for any particular purpose, and no warranty or representation shall be implied by law or otherwise. Any products sold by Indestructible Paint Ltd are not warranted as suitable for any particular purpose to the buyer. The suitability of any products for any purpose in particular to the buyer is for the buyer to determine. Indestructible Paint Ltd assumes no responsibility for the selection of products suitable to the particular purpose of any particular buyer. Indestructible Paint Ltd shall in no event be liable for any special, incidental or consequential damages.	
Safety Data Sheets:	For Safety Data Sheets pleas	e contact our Sales Department:
	Tel: +44(0)121 702 2485	
	Email: sales@indestructible.c	o.uk

Indestructible Paint Ltd, 16-25 Pentos Drive, Sparkhill, Birmingham B11 3TA Tel: +44(0)121 702 2485, Fax: +44 (0)121 778 4338, E-Mail: <u>sales@indestructible.co.uk</u>, Web: <u>www.indestructible.co.uk</u> Registered in England: 1376995