

---

**Product Name:**

Air Dry Red Oxide Anti-Corrosive Primer

---

**Product Number:**

IP2066

---

**Product Description:**

Fast Dry, air drying anti corrosive primer, formulated on the latest generation of chrome free anti-corrosive pigments. Pigmented to give a dark blue-red oxide colour.

---

**Approvals/Specifications:**

Approved by Meggitt-Dunlop, 2007, to replace S2 on aircraft braking parts, specifically braking wear surfaces and linings.

---

**Performance:**

Tack free physical air drying after approximately 30 minutes. Over coating time approximately 1 hour. Maximum resistance to solvents after 7 days air drying. Resistant to corrosion, fuels, oils and grease.

---

**Components:**

Single Component Coating – Thinner 985-Reducer or S01 may be added for spray application.

---

**Application:****Surface Preparation:**

Ensure surfaces are clean and free from dust, dirt etc.

Degrease and preferably pre-treat metals surfaces with phosphate or chromate pre-treatment or etch primer. May be applied to clean bare metal surfaces.

**Paint Preparation:**

Stir well before use. For part full containers ensure that the product has not skinned and any dry material around the can lip is not mixed into the coating before use.

**Application Method:**

Apply by Conventional, HVLP or Air less Spray.

Can be adjusted for Electrostatic Spray: Refer to our Technical Department.

---

Can be brush applied on small areas as a touch up.

Can be applied at supply viscosity; normally thinned 10-20% by volume.

## Drying Curing:

**Touch Dry:** 30 minutes

**Handleable:** 1 – 1.5 hour

**Hard Dry for Packing:** 24 hours

## Technical Properties:

**Supply Viscosity:** 70-80 secs, ISO 5 cup @23°C

**Flash Point:** 26°C

**VOC Content:** 490 g/litre

**Colour:** Red Oxide

**Pack Size:** 5 litre

**Density:** 1.31 kg/l

**Gloss:** Matt

**Thinner:** 985-Reducer or S01

**Solvent/Clean Up:** 40006 Gun Cleaner

**Catalyst:** N/A – single part product

**Theoretical Coverage:** 13 m<sup>2</sup>/lt

## Storage:

Highly flammable liquid: store and use in accordance with the flammable liquid regulations

**Shelf Life:** 12 months temperate; 6 months tropical

**Before use, refer to Product Safety Data Sheet**

## Disclaimer:

The information printed in this publication is based upon the research and experience of Indestructible Paint Ltd. No representation of warranty is made, however, concerning the accuracy or completeness of the information presented in this publication. Indestructible Paint Ltd make no warranty or representation of any kind, express or implied. Including without information limitation any warranty or merchantability or fitness for any particular purpose, and no warranty or representation shall be implied by law or otherwise. Any products sold by Indestructible Paint Ltd are not warranted as suitable for any particular purpose to the buyer. The suitability of any products for any purpose in particular to the buyer is for the buyer to determine. Indestructible Paint Ltd assumes no responsibility for the selection of products suitable to the particular purpose of any particular buyer. Indestructible Paint Ltd shall in no event be liable for any special, incidental or consequential

# Technical Data Sheet



---

## Safety Data Sheets:

For Safety Data Sheets please contact our Sales Department:

Tel: +44(0)121 702 2485

Email: [sales@indestructible.co.uk](mailto:sales@indestructible.co.uk)