Technical Data Sheet



Product Name:	Smoothseal A/D Touch Up
Product Number:	IP2376-001
Product Description:	High temperature one part Smoothseal touch up coating. The coating is designed to air dry, for spray or brush appliecation. Will withstand operating temperatures up to 600°C and provides good solvent and chemical resistance. Designed for use on jet engines and jet pipes.
Approvals/Specifications:	This coating is intended as an air drying touch up for Smoothseal. Refer to end user coating manuals for areas of application.
Performance:	Tack free physical air drying after approximately 30 minutes. Over coating time approximately 1 hour. Maximum resistance to solvents after 24-48 hours. To achieve optimum properties the coating should be run for 2-4 hours at temperatures of above 180°C.
Components:	Single component product designed for spray or brush application. May be thinned up to 15% by volume with AD-THIN.
Application:	
Surface Preparation:	All substrate must be clean, grease, oil, and finger print free. Any contamination will affect the heat resistance of the coating.
	This coating is designed for application as a touch up for Smoothseal that has be applied over cured IP9183-R1.
Paint Preparation:	Stir well before use. May be thinned with up to 15% AD-THIN by volume.
Application Method:	Designed for Spray or Brush application. Recommended dry film thickness 25-45 microns

Technical Data Sheet



Drying Curing:

This coating air dries at room temperature to provide a handleable coating. Full coating properties are achieved once the coating has been subjected to minimum 190°C for 1 hour.

Technical Properties:

Supply Viscosity: Spray applied

Flash Point: 21-28°C

VOC Content: 480 g/l

Colour: Yellow / Buff

Pack Size: 1 Litre

Density: 1.2kg/l

Gloss: Low Sheen

Thinner: AD-THIN

Solvent/Clean Up: AD-THIN

Catalyst: N/A

Theoretical Coverage: 10 sq/m litre

Storage:

Highly flammable liquid: store and use in accordance with the flammable liquid regulations

Shelf Life: 12 months temperate; 6 months tropical

Before use, refer to Product Safety Data Sheet

Disclaimer:

The information printed in this publication is based upon the research and experience of Indestructible Paint Ltd. No representation of warranty is made, however, concerning the accuracy or completeness of the information presented in this publication. Indestructible Paint Ltd make no warranty or representation of any kind, express or implied. Including without information limitation any warranty or merchantability or fitness for any particular purpose, and no warranty or representation shall be implied by law or otherwise. Any products sold by Indestructible Paint Ltd are not warranted as suitable for any particular purpose to the buyer. The suitability of any products for any purpose in particular to the buyer is for the buyer to determine. Indestructible Paint Ltd assumes no responsibility for the selection of products suitable to the particular purpose of any particular buyer. Indestructible Paint Ltd shall in no event be liable for any special, incidental or consequential damages.

Safety Data Sheets:

For Safety Data Sheets please contact our Sales Department:

Tel: +44(0)121 702 2485

Email: sales@indestructible.co.uk