
Product Name: High Temperature Ceramic Bonding Agent

Product Number: IP2902TM

Product Description: IP2902TM is an Inorganic High Temperature Ceramic Bonding agent that matures to a machinable, highly bonded, insoluble surface layer. The matured coating is designed to be unaffected by hot and cold water, mineral spirits, jet fuel, hydraulic oils, hot degreasing vapours and is resistant to temperatures up to 540°C, (1000F). designed as a non chrome alternative to Sermabond 481

Approvals/Specifications: - Safran Helicopter Engine (Turbomeca –) spec CCT600

Performance:

IP2902TM matured for the following schedules:

- Air Dry 24 hours @ room temperature followed by 4 hours @ 80°C (175F)
- Air Dry 24 hours @ room temperature followed by 4 hours @ 100°C (212F)
- Air Dry 24 hours @ room temperature followed by 4 hours @ 350°C (662F)

Heat Resistance: prolonged exposure to 540°C (1000F)

Organic Solvent and Oil tests:

Jet Fuel	- unaffected
Mineral spirit	- unaffected
Lubricating Oil	- unaffected
Water (room temperature)	- unaffected
Water (70°C)	- unaffected
Skydrol (70°C, 3 hours)	- unaffected

Application:

Surface Preparation:

Surfaces must be clean, grease and oil free and clear of any prior coatings.

For optimum performance the substrate should be vapour de-greased using 1,1,1-trichloroethane or equivalent. Grit blast with 90-120 aluminium oxide grit to produce a surface profile suitable for bonding.

Paint Preparation:

Mix the powder part A into part B liquid. Mix thoroughly to ensure that a homogenous mixture with no large agglomerates is produced. Any large powder agglomerates may be broken down to facilitate thorough mixing.

The mixed product must be allowed to stand for a minimum of 8 hours before use.

The product is supplied pre-weighed. Mix part A and part B as supplied.

Application Method:

The matured paste can be applied in open areas with appropriate spatulas or straight blades. In narrow or confined areas the paste may be applied using a syringe or sealant gun method.

Application equipment can be cleaned in warm water. Where a syringe or sealant gun is used the tip should be wiped clean between applications to prevent material blockages.

Drying Curing:

Air Dry 24 hours @ room temperature followed by 4 hours @ 80°C (175°F)

Air Dry 24 hours @ room temperature followed by 4 hours @ 100°C (212°F)

Air Dry 24 hours @ room temperature followed by 4 hours @ 350°C (662°F)

Technical Properties:

Supply Viscosity:	Two part ready to mix product. Viscosity increases to give a paste after minimum 8 hour induction time.
Flash Point:	N/A
VOC Content:	0 g/litre
Colour:	Grey
Pack Size:	1 Kg kit; 600gm fluid part A 400gm Powder Part B
Specific Gravity:	1.76 g/ml (mixed product)
Gloss:	Matt
Thinner:	de-mineralised or de-ionised water
Solvent/Clean Up:	Water
Catalyst:	N/A
Theoretical Coverage:	0.4 m ² @ 500 micron dft

Storage:

Water Based Material – store above 5°C (>5°C).

Shelf Life: 12 months temperate; 6 months tropical

Before use, refer to Product Safety Data Sheet

Disclaimer:

The information printed in this publication is based upon the research and experience of Indestructible Paint Ltd. No representation of warranty is made, however, concerning the accuracy or completeness of the information presented in this publication. Indestructible Paint Ltd make no warranty or representation of any kind, express or implied. Including without information limitation any warranty or merchantability or fitness for any particular purpose, and no warranty or representation shall be implied by law or otherwise. Any products sold by Indestructible Paint Ltd are not warranted as suitable for any particular purpose to the buyer. The suitability of any products for any purpose in particular to the buyer is for the buyer to determine. Indestructible Paint Ltd assumes no responsibility for the selection of products suitable to the particular purpose of any particular buyer.

Technical Data Sheet



Safety Data Sheets:

For Safety Data Sheets please contact our Sales Department:

Tel: +44(0)121 702 2485

Email: sales@indestructible.co.uk