

Technical Data Sheet



Product Name: Def Stan 80-217

Product Number: IP80-217

Product Description:

Temporary protective coating formulated from processed, highly refined mineral oils with water displacing, corrosion inhibitor, metal wetting and penetrating additives.

Temporary protection is a fast drying, thixotropic fluid that is solvent free and will not dry out.

This material has been dyed green in the past to show where it gets to.

Our material will be natural coloured unless specified.

Approvals/Specifications:

- Def Stan 80-217
- Joint Services Designation PX-1
- Rolls Royce OMAT 1005D
- (Nato interoperability Code) C 614

PX-1 is still widely used for short-term preservation and protection of certain components such as engine cylinders, valve gear, complete engines, gun barrels, ferrous and light allow sheets etc, in storage in temperate climates.

PX-1 is suitable for application by brushing, spraying or dipping

Performance:

For general use of aircraft components and metal surfaces liable to corrode during storage

Components:

Single part product supplied ready for use. Where necessary the coating may be thinned with White Spirit.

Technical Data Sheet



Application:

Surface Preparation:	To ensure that all surfaces are clean and free from dirt
Paint Preparation:	Stir well before use.
Application Method:	<p>Settles in the can; must be shaken before use. Apply by brushing, spray and immersion. The product can be removed with kerosene, gasoline, white spirits, solvent wipes etc.</p> <p>After application the solvent evaporates to leave a thin, soft film which hardens softly with age. The film is not hard enough to be handled and articles coated in it should be wrapped in grease resistant wrapping if necessary.</p> <p>The film normally dissolves in lubricating oil, but articles coated in it should preferably be cleaned before use.</p>
Drying Curing:	Air drying coating

Technical Properties:

Supply Viscosity:	Ready for Use
Flash Point:	>41°C
VOC Content:	575 g/l
Colour:	Clear or Green
Pack Size:	20 Litres UN Approved Cans
Density:	0.83kg/l
Gloss:	N/A
Thinner:	White Spirit
Solvent/Clean Up:	40006
Catalyst:	N/A
Theoretical Coverage:	10 sq/m litre

Storage:

Highly flammable liquid: store and use in accordance with the flammable liquid regulations

Shelf Life: 12 months temperate; 6 months tropical

Before use, refer to Product Safety Data Sheet

Disclaimer:

The information printed in this publication is based upon the research and experience of Indestructible Paint Ltd. No representation of warranty is made, however, concerning the accuracy or completeness of the information presented in this publication. Indestructible Paint Ltd make no warranty or representation of any kind, express or implied. Including without information limitation any warranty or merchantability or fitness for any particular purpose, and no warranty or representation shall be implied by law or otherwise. Any products sold by Indestructible Paint Ltd are not warranted as suitable for any particular purpose to the buyer. The suitability of any products for any purpose in particular to the buyer is for the buyer to determine. Indestructible Paint Ltd assumes no responsibility for the selection of products suitable to the particular purpose of any particular buyer. Indestructible Paint Ltd shall in no event be liable for any special, incidental or consequential damages.

Safety Data Sheets:

For Safety Data Sheets please contact our Sales Department:

Tel: +44(0)121 702 2485

Email: sales@indestructible.co.uk