## **Technical Data Sheet**



Product Name:	Shellac L	Shellac Lacquer 6%				
Product Number:	IP80-44-6					
Product Description:	Def Stan 80	Def Stan 8044 was cancelled in October 2002				
		This is an obsolete specification but this product still complies with the original Defence Standard				
	The lacque	The lacquers are used in the manufacture of armaments				
		Lacquer Shellac 6%: Coating brass components, the lacquer is normally tinted orange for this purpose				
		Please note that the QX release has been cancelled and users need to test for capability themselves.				
Approvals/Specifications:	(unforte	<ul> <li>Complies to the cancelled specification of Def Stan 80-44 (unfortunately we can no longer state this specification on our paperwork)</li> </ul>				
		- Can also be other solids contents, including 40%, 30%, 20%, 14.5%, 11%				
Performance:		IP80-44-11 complies with the testing requirements of Def Stan 80- 44, they are as follows:				
	Property	System / Substrate	Requirement	Method of Test		
	Non-Volatile Matter (m / m)	-	11% (6±0.5%)	BS 3900 Part B18		
	Application Propertie and Finish	s Single coat, burnished steel	Clear, Smooth, Hard continuous film	Visual, 24 hours after application		
	Hard Dry Time	Single coat, Burnished tinplate	≤ 30 Minutes	BS EN 29117		

Indestructible Paint Ltd, 16-25 Pentos Drive, Sparkhill, Birmingham B11 3TA Tel: +44(0)121 702 2485, Fax: +44 (0)121 778 4338, E-Mail: <u>sales@indestructible.co.uk</u>, Web: <u>www.indestructible.co.uk</u> Registered in England: 1376995

# **Technical Data Sheet**



Components:	Single Pack Product. May be thinned for application by using Cellulose Thinner 18802			
Application:				
Surface Preparation:	To ensure that all surfaces are clean and free from dirt			
Paint Preparation:	Ready for use			
Application Method:	Dip, Spray or Brush			
Drying Curing:	Air Dry: Air drying product Heat Cure: May be force dried if required			
Technical Properties:	Supply Viscosity:	Solvent Viscosity		
	Flash Point:	12°C		
	VOC Content:	780 gm / per litre		
	Colour:	Amber		
	Pack Size:	-		
	Density:	0.8 g / ml		
	Gloss:	N/A		
	Thinner:	-		
	Solvent/Clean Up:	Cellulose Thinner 18802		
	Catalyst:	N / A		
	Theoretical Coverage:			
Storage:	Highly flammable liquid: store and use in accordance with the flammable liquid regulations			
	Shelf Life: 12 months temperate; 6 months tropical			
	Before use, refer to Product Safety Data Sheet			

Indestructible Paint Ltd, 16-25 Pentos Drive, Sparkhill, Birmingham B11 3TA Tel: +44(0)121 702 2485, Fax: +44 (0)121 778 4338, E-Mail: <u>sales@indestructible.co.uk</u>, Web: <u>www.indestructible.co.uk</u> Registered in England: 1376995

### **Technical Data Sheet**



#### **Disclaimer:**

The information printed in this publication is based upon the research and experience of Indestructible Paint Ltd. No representation of warranty is made, however, concerning the accuracy or completeness of the information presented in this publication. Indestructible Paint Ltd make no warranty or representation of any kind, express or implied. Including without information limitation any warranty or merchantability or fitness for any particular purpose, and no warranty or representation shall be implied by law or otherwise. Any products sold by Indestructible Paint Ltd are not warranted as suitable for any particular purpose to the buyer. The suitability of any products for any purpose in particular to the buyer is for the buyer to determine. Indestructible Paint Ltd assumes no responsibility for the selection of products suitable to the particular purpose of any particular buyer. Indestructible Paint Ltd shall in no event be liable for any special, incidental or consequential damages.

### Safety Data Sheets:

For Safety Data Sheets please contact our Sales Department:

Tel: +44(0)121 702 2485

Email: sales@indestructible.co.uk