

Technical Data Sheet



Product Name: General Service Gloss Finishing Paint
Fuel Resistant – Low VOC

Product Number: IP80-54

Product Description: This standard specifies for the requirements for a fuel resistant gloss finishing paint suitable for application by either brush or spray. The air drying paint is suitable for interior and exterior use and may be used with an appropriate priming paint on prepared and / or pre-treated ferrous and wood substrates. The finish is available in a number of colours mainly from BS 381 C – please specify the colour when placing an order.

Approvals/Specifications: - Def Stan 80-54

Performance:

- **Resistance to mineral oil** – 96 hours after application
- **Resistance to liquid fuel** – 7 days after application
- **Resistance to artificial weathering** – Using UVA 351 lamps for a period of 8 weeks, 7 days after application
- **Resistance to continuous salt spray** – for a period of 10 days, 7 days after application
- **Resistance to heat** – for a period of 24 hours, 7 days after application

Components: Single Pack Product. May be thinned for application by using IP80-54 Thinner

Technical Data Sheet



Application:

Surface Preparation:	Minimum Degrease; Grit Blast recommended
Paint Preparation:	Thin as required
Application Method:	Brush or Conventional Spray
Drying Curing:	Air Dry: <ul style="list-style-type: none">- ≤ 4 hours Surface Dry- ≤ 16 hours Hard Dry

Technical Properties:

Supply Viscosity:	80 Secs / ISO 6 cup / 23°C
Flash Point:	≥32°C
VOC Content:	<420 Grams Per Litre
Colour:	BS 381C Range
Pack Size:	-
Density:	0.925 – 1.175kg/l
Gloss:	Full Gloss
Thinner:	IP80-54 Thinner
Solvent/Clean Up:	40006 or IP80-54 Thinner
Catalyst:	-
Theoretical Coverage:	12-15 square meters per litre

Storage:

Flammable liquid: store and use in accordance with the flammable liquid regulations

Shelf Life: 12 months temperate; 6 months tropical

Before use, refer to Product Safety Data Sheet

Disclaimer:

The information printed in this publication is based upon the research and experience of Indestructible Paint Ltd. No representation of warranty is made, however, concerning the accuracy or completeness of the information presented in this publication. Indestructible Paint Ltd make no warranty or representation of any kind, express or implied. Including without information limitation any warranty or merchantability or fitness for any particular purpose, and no warranty or representation shall be implied by law or otherwise. Any products sold by Indestructible Paint Ltd are not warranted as suitable for any particular purpose to the buyer. The suitability of any products for any purpose in particular to the buyer is for the buyer to determine. Indestructible Paint Ltd assumes no responsibility for the selection of products suitable to the particular purpose of any particular buyer. Indestructible Paint Ltd shall in no event be liable for any special, incidental or consequential damages.

Safety Data Sheets:

For Safety Data Sheets please contact our Sales Department:

Tel: +44(0)121 702 2485

Email: sales@indestructible.co.uk