Technical Data Sheet



Product Name:	Air Drying Blade Root Sealing Compound
Product Number:	PL224
Product Description:	Designed for filling and sealing compressor blade roots at high temperatures with resistance to aircraft fluids and minimum expansion and contraction up to 400°C (750°F)
Approvals/Specifications:	 MSRR 9298 OMat 844 Rolls Royce Code: 136668
Performance:	Resistant to a wide range of fuels, oils, solvents and heat up to 650°C (1,205°F). After a minimum of 24 hours air drying, this product will stand up to 400°C (750°F) for 4 hours without cracking.
Components:	Single Pack Product. May be thinned for application using water.
Application:	
Surface Preparation:	Ensure that all surfaces are clean and free from dirt
Paint Preparation:	Stir to an even paste prior to application
Application Method:	Apply by spatula, where splashes and material need removing prior to stoving this can be done with a damp cloth or water
Drying Curing:	1 hour at room temperature

Technical Data Sheet



Technical Properties:	Supply Viscosity:	Paste	
	Flash Point:	Water Based – non-flammable	
	VOC Content:	Paste	
	Colour:	Off White / Grey	
	Pack Size:	1 Kilo	
	Density:	1.69 g/ml	
	Gloss:	N/A	
	Thinner:	Water	
	Solvent/Clean Up:	Water	
	Catalyst:		
	Theoretical Coverage:	.5 sq m/kg @ 80 micron	
Storage:	Highly flammable liquid: store and use in accordance with the flammable liquid regulations		
	flammable liquid regulations		
	Shelf Life: 12 months tempera	ate; 6 months tropical	
Disclaimer:	Shelf Life: 12 months tempera Before use, refer to Product The information printed in this publica Indestructible Paint Ltd. No represent accuracy or completeness of the infor Paint Ltd make no warranty or represent without information limitation any warr purpose, and no warranty or represent products sold by Indestructible Paint L purpose to the buyer. The suitability of buyer is for the buyer to determine. In the selection of products suitable to the		
Disclaimer: Safety Data Sheets:	Shelf Life: 12 months tempera Before use, refer to Product The information printed in this publica Indestructible Paint Ltd. No represent accuracy or completeness of the infor Paint Ltd make no warranty or represent without information limitation any warr purpose, and no warranty or represent products sold by Indestructible Paint L purpose to the buyer. The suitability of buyer is for the buyer to determine. In the selection of products suitable to the Indestructible Paint Ltd shall in no ever consequential damages.	Safety Data Sheet tion is based upon the research and experience of tation of warranty is made, however, concerning th mation presented in this publication. Indestructible entation of any kind, express or implied. Including anty or merchantability or fitness for any particular tation shall be implied by law or otherwise. Any td are not warranted as suitable for any particular of any products for any purpose in particular to the indestructible Paint Ltd assumes no responsibility for the particular purpose of any particular buyer.	

Indestructible Paint Ltd, 16-25 Pentos Drive, Sparkhill, Birmingham B11 3TA Tel: +44(0)121 702 2485, Fax: +44 (0)121 778 4338, E-Mail: <u>sales@indestructible.co.uk</u>, Web: <u>www.indestructible.co.uk</u> Registered in England: 1376995